

Gemini System

60.0", 72.0", 84.0", and 96" width units

SPECIFICATION WORKSHEET - SINGLE OR DOUBLE-SIDED, TWIN-TUBE SUPPORT FRAME

RACEWAY ELECTRIC (Per Side *)

1-120VAC, 20Amp GFI Duplex

1-USB x4 charging outlet

1-20 Amp GFI / USB x2 combo

RACEWAY ELECTRIC (Per Side *)

1-120VAC, 20Amp GFI Duplex

1-USB x4 charging outlet

1-20 Amp GFI / USB x2 combo

RACEWAY ELECTRIC (Per Side *)

1-120VAC, 20Amp GFI Duplex

1-USB x4 charging outlet

1-20 Amp GFI / USB x2 combo

DATA PORTS (Left Post)

RJ45 (shielded)

x1

x2

LOWER ELECTRIC (Left Post)

pre-wired as selected below

1-120VAC, 20Amp GFI Duplex

1-USB Charging Outlet

1-20 Amp GFI / USB x2 combo

NONE

WIDTH OF UNIT

60.0"

72.0"

84.0"

96.0"

ELECTRICAL OUTLET COLOR

WHITE

BLACK

BENCH FRAME COLOR _____

Swap Sides, Plumbing on Left, Data on Right on GS1

SERVICES (Right Post)

pre-plumbed to top of upright

see below for options

_____ indicate service required

_____ indicate service required

_____ indicate service required

MODESTY PANEL (non-adjustable) height at 36"

Yes

No

Single-Sided Bench

Double-Sided Bench

30.0" Table Depth (per side)

36.0" Table Depth (per side)

POWER

PLUMBING

- ELECTRICAL WIRING OPTIONS
- Single-circuit 20A, 1- Straight-blade plug, 1 cord
 - Double-circuit 20A, 2- Straight-blade plugs, 2 cords
 - Single-circuit 20A, 1- Twist-lock plug, L5-20P (1x120v), 1 cord
 - Double-circuit 20A, 2- Twist-lock plugs, L5-20P (2x120v), 2 cords
 - Double-circuit 20A, 1- Twist-lock plug, L14-20P (1x240v), 1 cord
 - Quad-circuit 20A, 2- Twist-lock plugs, L14-20P (2x2400v), 2 cords
- Specified length (top of bench to ceiling) _____

- ELECTRICAL PIGTAIL EXIT LOCATION
- Side above plumbing services
 - Side opposite plumbing services
 - Exit post near bottom
- GS1- Single-Sided:
- Exiting LEFT-SIDE
 - Exiting RIGHT-SIDE

SEE PLUMBING ILLUSTRATION ON SECOND PAGE FOR HOSE TYPES, CONNECTIONS, and FIXTURES. SPECIFY IF BURNING GAS, OXYGEN, OR CLEAN GAS REQUIRED.

-Your notes:

GS _ - _ - _ P _ D _ E

example: **GS2-4830-3P2D7E**

Single-Sided = 1

Double-Sided = 2

48" wide X 30" deep (per side)

3 Plumbed Services

2 Data Ports

7 Electrical (inc lower)

(Sold Separately)



A
 Fixture to Ceiling
 1/2" or 5/8" PVC HOSE
 or 1/2" Braided Stainless
 w/ Male Quick-Connect

B
 Internal
 1/2" PVC HOSE
 or 1/2" Braided Stainless

Junction
 Keyed set Male/ Female
 Quick-Connects

External
 1/2" or 5/8" PVC HOSE
 w/ Male Quick-Connect


C
 Internal
 1/2" PVC HOSE
 or 1/2" Braided Stainless
 w/ Male Quick-Connect



Bench




	A	B	C
PVC HOSE	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
STAINLESS HOSE	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>




Single, Needle Valve - Black Knob

FINISH: _____




Single, Needle Valve - ColorTech Knob

FINISH: _____




Double, Needle Valve - Black Knobs

FINISH: _____



Double, Needle Valve - ColorTech Knobs

FINISH: _____



Double, Ball Valve - Lever Handles

FINISH: _____

(There is a maximum of three fixtures per side)