

Gemini System

36.0" 42.0" and 48" width units

SPECIFICATION WORKSHEET - SINGLE OR DOUBLE SIDED, TWIN-TUBE SUPPORT FRAME

RACEWAY ELECTRIC
Reference page 3 for selection sheet

DATA PORTS (Left Post)
RJ45 (shielded)

NONE

LOWER ELECTRIC (Left Post)
pre-wired as selected below

NONE

WIDTH OF UNIT

48.0"

*60" & 72" can be manufactured with single full width shelf

TABLE DEPTH

30.0" Table Depth (Per Side)

SLOT 1 SLOT 2 SLOT 3

ELECTRICAL OUTLET COLOR
WHITE
If other, specify: _____

BENCH FRAME COLOR
OFF WHITE
If other, specify: _____

**Per Side when GS2 Double-Sided Bench is selected.

SERVICES (Right Post)
pre-plumbed to top of upright
see below for options

NONE indicate service required

NONE indicate service required

NONE indicate service required

MODESTY PANEL
(non-adjustable) height at 36"

Yes ☐

No ☐

SINGLE / DOUBLE SIDED

Single-Sided Bench

☐ Swap Sides, Plumbing on Left, Data on Right on GS1

POWER

ELECTRICAL WIRING OPTIONS

N/A

Specified length (top of bench to ceiling) _____

ELECTRICAL PIGTAIL EXIT LOCATION

N/A

GS1- Single-Sided:

N/A

5-20P

L5-20P

L14-20P

DATA

DATA EXIT LOCATION

N/A

Specified length (top of bench to ceiling) _____

PLUMBING

SEE PLUMBING ILLUSTRATION ON SECOND PAGE FOR HOSE TYPES, CONNECTIONS, and FIXTURES. PLEASE SPECIFY IF BURNING GAS, OXYGEN, OR CLEAN GAS REQUIRED

-Your notes:

GS - - **P** **D** **E**

example: **GS2-4830-3P2D7E**

Width Depth 3 Plumbing Services 7 Electrical (Including lower)

Single-Sided = 1 / Double-Sided = 2 2 Data Ports



GEMINI BENCH




example: **GSK-1535-12B**

Width Bracket Depth

Full Shelf Depth* Bracket Type

*This includes the 1" OR 3" extensions added to back edge.

Bracket Types:



Gemini Width	Does it allow split shelving?	Part Numbers Needed
36"	Single Only	GSK-__34-__
42"	Single Only	GSK-__40-__
48"	Single Only	GSK-__46-__

Bracket Selection:

N/A

Bracket ONLY:

☐ ONLY Brackets*
No shelves

*For purchases with alternative shelving.

Depth*: *Depth w/o extensions

N/A

Shelf Depth Extension:

None



Quantity:

None

Width:

N/A

Comments:




Gemini System

36.0" 42.0" and 48" width units

SPECIFICATION WORKSHEET - PLUMBING

Specified length (top of bench to ceiling) _____

(Sold Separately)



A
Fixture to Ceiling
1/2" or 5/8" PVC HOSE
or 1/2" Braided Stainless
w/ Male Quick-Connect

B
Internal
1/2" PVC HOSE
or 1/2" Braided Stainless

Junction
Keyed set Male/ Female
Quick-Connects

External
1/2" or 5/8" PVC HOSE
w/ Male Quick-Connect

C
Internal
1/2" PVC HOSE
or 1/2" Braided Stainless
w/ Male Quick-Connect

PVC HOSE

STAINLESS HOSE

A



B




C



(There is a maximum of three fixtures per side)

*4 Plumbing services maximum through Broen. Please contact AMS for Broen product information.




INV010-16-14BV

Single, Needle Valve - Black Knob



FINISH: _____




CT2880

Single, Needle Valve - ColorTech Knob



FINISH: _____




INV010-16-14BV-VR-WSA

Double, Needle Valve - Black Knobs



FINISH: _____




CT3180-332S

Double, Needle Valve - ColorTech Knobs



FINISH: _____



L4200

Double, Ball Valve - Lever Handles



FINISH: _____

AMS
standards you deserve

Gemini System

36.0" 42.0" and 48" width units

SPECIFICATION WORKSHEET - RACEWAY ELECTRICAL



- Black
- Brown
- Gray
- Ivory
- Light Almond
- White

120VAC, 20Amp GFI Duplex



- Black
- Gray
- Ivory
- Light Almond
- White

USB Charging Outlet



- Black
- Brown
- Gray
- Ivory
- Red
- Light Almond
- White

20Amp GFI / USB x2 Combo



RJ45 Shielded Coupler

Gemini Systems 36.0", 42.0", and 48.0" Width Units allow **up to 4** GFI slots on the top raceway.

Double-sided allow **up to 8** GFI slots on the top raceway.

From Left to Right facing front of bench. ➤

SLOT 1

NONE

SLOT 2

NONE

SLOT 3

NONE

SLOT 4

NONE

Slots 5 - 8 (Use only if Double-Sided)

SLOT 5

NONE

SLOT 6

NONE

SLOT 7

NONE

SLOT 8

NONE